



NVX-3000

NAVTEX RECEIVER



NSR'S NEW GENERATION NAVTEX RECEIVER

- MED / Wheelmark type approved by DNV-GL
- Large 7-inch color LCD display with touchscreen
- Superhigh sensitive radio technology software
- Receives 3-channels simultaneously
- Reliable quality
- BAM compatible

NVX-3000 NAVTEX RECEIVER



The NSR NVX-3000 Navtex is a dual-channel NAVTEX receiver for SOLAS ships complying with the new NAVTEX performance standard MSC.148(77) which is implemented on and after 1 July 2005.

Features

- | | |
|--|---|
| <ul style="list-style-type: none"> Large 7-inch color LCD display Receive simultaneously three IMO NAVTEX frequencies (518 kHz, 490 kHz and 4209.5 kHz) Displays the message contents Messages stored for 72 hours Simple to operate by touchscreen | <ul style="list-style-type: none"> Desktop or flush mount External printer output External BAM/INS interface Low power consumption Self-diagnosis function |
|--|---|

Specifications

NAVTEX Receiver

Receiving Frequencies: 518 kHz, 490 kHz & 4209.5 kHz, to receive on three channels simultaneously

Mode: F1B

Sensitivity: Better than -110 dBm

Environmental condition

Temperature Range: -20°C ~ +55°C operational,

-30°C ~ +70°C storage (Antenna & Amplifier)

IP Grade: IP22 (Receiver), IP66 (Antenna & Amplifier)

Compass safe distance: 1.15 m (standard)

Display

Display System: 7-inch, color LCD, touchscreen operation, 154(W) × 87(H) mm

Resolution: 800 x 480 px

Character number: English 40 characters / line

Interface

Input sentences of NMEA IN port: ZDA, RMC

Input sentences of INS port: NRM, CRQ, ACK, CAN

Output sentences of INS port: ALR, NRX, NRM, ACN, ACK, ALF, ALC, ARC, HBT

Power supply

DC 24 V (10 V ~ 38 V, 10 W average)

Weight

2.3 kg (Receiver)

Dimension

264(W) × 145(H) × 80(D) mm (Receiver)

125(L) × 125(W) × 110(H) mm (Antenna)

Equipment list

Standard

Receiver: 1 pc

H-field antenna (NXA-200) w/ 20 m cable: 1 pc


Accessories: 1 set

Options

Printer (NPT-100): 1 pc

AC/DC PSU: 1 set

System diagram and dimensions



Distributor



More information at rcom.nl

+31 (0)180 - 62 24 42

Manufacturer

New Sunrise Co., Ltd.

nsrmarine.com

